

Large Format Media Product Information Document

1929B Glacier Photo Quality Paper 300 g/m²

Description

This top quality photo inkjet paper has a quality photo coating for high grade natural colour prints of graphic pictures, presentations and photos. The paper is instant dry, is smudge resistant and provides good colour density and excellent image sharpness. This paper is compatible with a large range of dye and pigment digital printing systems, and is the most ideal product for users who need top quality photographic re-productions. 1929B Glacier Photo Quality Paper 300 g/m² is PEFC certified.

Features

Extremely quick drying, dye and pigment ink compatible, good colour density, excellent image sharpness, smudge resistant, lamination not necessary, easy handling.

Applications

Photography, portraits, posters, graphic art reproductions, exhibition graphics, indoor and outdoor signage.

Available widths / PEFC certification

Article number	Width (mm)	Length (m)	Order Multiple	Mercury Code
97003078	432	30	1	1929B001AA
97003079	610	30	1	1929B002AA
97003080	914	30	1	1929B003AA
97003081	1067	30	1	1929B004AA
97003082	1270	30	1	1929B005AA
97003083	1524	30	1	1929B006AA



Compatibility and profiles

Advised Driver / panel settings: HW Satin Photo Paper / HW Satin Photo
Refer for Onyx and other profiles to www.mediaguide.oce.com
Select your Canon printer to find matching media and media profiles.

Printing

For optimum results select the best possible print settings.

Lamination

To add surface protection from dirt, abrasion and gas-fading, lamination is recommended. Although ink drying is virtually immediate, it is still recommended to allow a waiting time of approximately 3 hours before lamination.

In order to prevent moisture ingress and paper splitting, lamination with a 5-6mm encapsulated edge is also recommended. Lamination must be evenly applied to the print in order to avoid curling. Both hot and cold lamination is possible.

Physical Properties

Weight	300 ±7 g/m ²
Calliper	288 ±5 microns
Gloss	45 ± 5
Whiteness	120 CIE

Storage Conditions

Store paper only in original boxes, out of direct sunlight and under normal climatic conditions (23 °C, 50% RH) until ready to use. Allow material to adapt to room conditions before use. Papers can absorb moisture in humid conditions or lose moisture in low humidity conditions. Highly humid conditions make the ink drying time longer and this could interfere with proper laminate adhesion.

Shelf Life

2 years from shipping date when stored under ideal conditions (see above)